




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G02B 1/28, G01B 11/00, G11C 13/04,</b> <b>G11B 7/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/43669</b> <b>(43) International Publication Date:</b> 20 November 1997 (20.11.97)
<b>(21) International Application Number:</b> PCT/US97/07780 <b>(22) International Filing Date:</b> 7 May 1997 (07.05.97)  <b>(30) Priority Data:</b> 08/644,810      10 May 1996 (10.05.96)      US  <b>(71) Applicant:</b> QUANTUM CORPORATION [US/US]; 500 McCarthy Boulevard, Milpitas, CA 95035 (US).  <b>(72) Inventors:</b> HAYS, Nathan, J.; 48 Thor Avenue, San Francisco, CA 94131 (US). HENSON, James, A.; 15250 Sycamore Drive, Morgan Hill, CA 95037 (US). CARPENTER, Christopher, M.; 549 S. Frances, Sunnyvale, CA 94086 (US). AKIN, William, R., Jr.; 1045 Brookview Court, Morgan Hill, CA 95037 (US). EHRLICH, Richard, M.; 12092 Marilla Drive, Saratoga, CA 95070 (US). BEAZLEY, Lance, D.; 1909 Quebec Way, San Jose, CA 95124 (US).  <b>(74) Agents:</b> HARRISON, David, B. et al.; Quantum Corporation, 500 McCarthy Boulevard, Milpitas, CA 95035 (US).		<b>(81) Designated States:</b> AU, CA, CN, JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** POSITION FEEDBACK SYSTEM FOR VOLUME HOLOGRAPHIC STORAGE MEDIA**(57) Abstract**

A method of holographic recording in a photorefractive medium wherein stored holograms may be retrieved with maximum signal to noise ratio (SNR) is disclosed. A plurality of servo blocks containing position feedback information is recorded in the crystal (200) and made non-erasable by heating the crystal (300). The servo blocks are recorded at specific increments, either angular or frequency, depending whether wavelength or angular multiplexing is applied, and each servo block is defined by one of five patterns. Data pages are then recorded at positions or wavelengths enabling each data page to be subsequently reconstructed with servo patterns which provide position feedback information. The method of recording data pages and servo blocks is consistent with conventional practices. In addition, the recording system also includes components (e.g. voice coil motor) which respond to position feedback information and adjust the angular position of the reference angle of a reference beam to maximize SNR by reducing crosstalk, thereby improving storage capacity.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## POSITION FEEDBACK SYSTEM FOR VOLUME HOLOGRAPHIC STORAGE MEDIA

### Field of the Invention

This invention relates to the field of holographic storage systems and  
5 methods. More particularly, this invention relates to a method for recording  
data in and reconstructing data from a photorefractive medium in the form  
of holograms, including a permanent hologram containing position feedback  
information.

### 10 Background of the Invention

The potential of volume holographic storage in photorefractive  
medium for large digital storage capacity, fast data transfer rates and short  
access times has been considered for some time. Recent developments in  
materials and holographic storage components have made the promise of  
15 data storage capacity in the magnitude of terabytes, transfer rates exceeding  
1 gigabyte per second and random access times less than 100 micro seconds  
closer to being realized.

Photorefractive materials have the property of developing light  
induced changes in their index of refraction. Holographic storage can be  
20 accomplished by propagating and recording an image-bearing light beam  
and a reference beam into a photorefractive medium. The resulting optical  
interference pattern causes a spatial index of refraction to be modulated  
throughout the volume of the medium. In a photo-refractive medium such  
as LiNbO<sub>3</sub> (lithium niobate), the spatial index of refraction gratings are  
25 generated through the electro-optic effect as a result of an internal electric  
field generated from migration and trapping of photoexcited electrons.  
When the medium is illuminated with a beam identical to the reference

beam used to generate the refractive index grating, the beam will diffract in such a way as to reproduce the original image bearing wavefront.

In a typical holographic storage system, shown in Fig. 1, a coherent monochromatic beam, projected from a light source 11, may be split into an object beam 24 and a reference beam 22 by a beam splitter 12. The object beam 24 is converted to an optical signal with a Spatial Light Modulator (SLM) 14. Through reducing optics 16 and 17, the object beam 24 and the reference beam 22 converge on and illuminate a photorefractive crystal 18, generating a volumetrically distributed interference pattern in the crystal 18 which is recorded in the form of a refractive index grating, otherwise known as a hologram. The recorded hologram may be reproduced by illuminating the crystal 18 with the identical reference beam 22 and imaging the diffracted optical signal onto a detector array 19, which converts the optical signal back into an electrical signal.

Multiple holograms, each corresponding to a data page, may be written and stored in the crystal 18, using various forms of multiplexing, e.g. angular, wavelength, etc.. Using angular multiplexing, each hologram is written with a reference beam incident at a different angle. The angles vary depending on the physical geometry and material of the crystal. Typically, angles may differ by a magnitude of about 50 micro radians. The angle may be changed either by mechanically translating the crystal 18 while keeping the object to reference angle constant or by changing the angle of incidence of the reference beam on the crystal by steering the reference beam angle with the reducing optics 16 and 17. With wavelength multiplexing, each hologram is generated with the reference beam fixed at some angle while changing the wavelength of the light source for each data page.

One limitation inhibiting the potential advantages of holographic recording is the metastable (impermanent) nature of recorded holograms.

When holograms are serially but coextensively recorded in the same volume of crystal, commonly referred to as "a stack" of recordings, subsequently recorded holograms tend to non-uniformly reduce the diffraction efficiency of previously written holograms. Thus, a "write" process destroys the  
5 previously recorded nearby holograms by fractionally reducing the previously recorded hologram's intensity over many write cycles. Similarly, a "read" process of exposing an area to a reference beam illumination will also cause a redistribution of the charges which make up the recorded hologram. This has led to the development of techniques for fixing and  
10 developing more permanent holograms. For example, holograms generated by electron charge patterns may be made permanent by heating the crystal, which results in redistributing the ions which cancel the space charge variation in the crystal. The crystal is thereafter cooled, trapping the ions and forming a permanent ionic grating to generate the index variation.

15 Another limitation inhibiting the potential application of holographic recording is cross talk during hologram retrieval, which limits the information density and storage capacity of a crystal. Because of the Bragg-selective nature of a readout, a stored image or data page may be reproduced independently from other pages of the stack of recordings. As discussed,  
20 retrieval is accomplished by illuminating the medium with a reference wavelength identical to the one used in recording that image. However, although Bragg-selectivity ensures that an image associated with a particular reference wavelength is reconstructed with the highest efficiency, other stored images may also be reconstructed with less efficiency and distortions  
25 due to Bragg-mismatch. To avoid this form of crosstalk, the angular or wavelength separation between holograms must precisely correspond to the zeros of the sinc function associated with the Bragg matching condition. Any deviation from the ideal angle degrades the signal-to-noise ratio (SNR).

The consequence is that either the maximum resolution of the image or the storage capacity of the system is reduced.

Many approaches have attempted to overcome this capacity limitation. However, none have utilized a closed loop position feedback system during data page retrieval to maximize SNR of the recorded signal by reducing crosstalk and precise angle positioning. Further, none have utilized a closed loop position feedback system combining permanent and metastable holograms within the same recording area. Thus, a hitherto unsolved need has remained for a method of holographic recording in a photorefractive medium which provides a position feedback system for maximizing SNR of the recorded signal by reducing crosstalk and is applicable to both angular and wavelength multiplexing.

#### **Summary of the Invention with Objects**

A general object of the present invention is to provide a method of holographic recording in a photorefractive medium which overcomes limitations and drawbacks of the prior art.

Specifically, an object of the present invention is to provide a method of holographic recording in a photorefractive medium having a position feedback system which maximizes SNR of the recorded signal by reducing crosstalk.

Another object of the present invention is to provide a method of holographic recording in a photorefractive medium wherein the position feedback system is applicable for both angular and wavelength multiplexing.

One more object of the present invention is to provide a method of holographic recording in a photorefractive medium having a position feedback system by combining permanent and metastable holograms.

In accordance with principles of the present invention, a holographic recording method first records a plurality of servo blocks in a photorefractive medium, such as an  $\text{LiNbO}_3$  crystal. Each servo block is defined by a five spot pattern. The servo blocks are generated by the simultaneous illumination of the crystal by an object and a reference beam on a same area of the crystal. The angle of incidence on a face of the crystal, by the reference beam, defines a reference angle. The servo blocks provide position feedback during reconstruction of data pages stored in the crystal, enabling data pages to be reconstructed with maximum SNR. The servo blocks are further recorded at reference angle increments of half the minimum angular separation of the crystal, which is determined by the physical dimensions of the crystal. The servo blocks are then made non-erasable (fixed) using methods known by those skilled in the art, e.g. by heating the crystal. Each of the five spots is recorded in the same image space as data pages so that position feedback information is retrieved along with a data page during hologram retrieval.

Data pages are then recorded in the same image space of the crystal in the same manner, i.e. by simultaneously illuminating the crystal with an image bearing object beam and a reference beam. The data pages are recorded at reference angle increments of the minimum angular spacing of the crystal. During a data page retrieval, position feedback information from the servo blocks is communicated to a reflector positioner, e.g. a voice coil motor. The positioner rotatably adjusts the angular position of a reflecting mirror to fine tune the reference angle of the reference beam thereby maximizing SNR of the recorded signal by reducing crosstalk.

### Brief Description of the Drawings

Fig. 1 is a schematic diagram of a typical prior art holographic recording system, using a photorefractive crystal.

Fig. 2 is a flow diagram of steps for achieving the holographic recording method in accordance with the present invention.

5 Fig. 3 illustrates one embodiment of a servo block for providing position feedback for the holographic recording method in accordance with principles of the present invention.

Figs. 4a-4e illustrate five patterns of the servo block of Fig. 3, in accordance with principles of the present invention.

10 Fig. 5 is a plot of data page amplitude as a function of angle of incidence of the reference beam.

Fig. 6 is a plot of servo block amplitude as a function of angle of incidence of the reference beam.

15 Fig. 7 is a plot of difference of position functions of Fig. 6 as a function of angle of incidence.

Fig. 8 is a plot of linearized positioning function as a function of angle of incidence of the reference beam.

Fig. 9 illustrates servo block sinc image intensities as a function of angle of incidence of the reference beam.

20 Fig. 10 is a schematic diagram of the holographic recording system for recording and reconstructing holograms in accordance with the present invention.

### **Detailed Description of a Preferred Embodiment**

25 Fig. 2 shows a flow diagram of the steps for achieving the method of holographic recording in accordance with the present invention. These steps include determining minimum angular spacing of the crystal 100, recording servo blocks in the crystal 200, heating the crystal to fix the servo blocks



300, quenching the crystal back to room temperature 400, recording data pages in the crystal 500, and reconstructing recorded data pages 600.

The first step 100, prior to recording any holograms, is determining a minimum angular spacing required to define separate holographic recordings in the photorefractive crystal such that crosstalk is minimized. The details in deriving an equation for determining the minimum angular spacing, are known to those skilled in the art. Specifically, such details are discussed and described in an article by John H. Hong et al., entitled "Volume holographic memory systems: techniques and architectures", *Optical Engineering*, Vol. 34, No. 8, August 1995, the article being incorporated herein by reference. Hong et al. defines the minimum angular spacing  $\theta$ , by the equation

$$\theta = \lambda \cos \theta_o / nL \sin(\theta_r + \theta_o) \quad (1)$$

15

where  $\lambda$  = wavelength of the signal,  $n$  = refractive index of the crystal,  $L$  = thickness of the crystal,  $\theta_r$  = angle of incidence of the reference beam with respect to the z-axis, and  $\theta_o$  = angle of incidence of the object beam with respect to the z-axis.  $\theta_r$  may be determined based on the geometry of the reducing optics and the crystal. Applying equation (1) to the embodiment illustrated in Fig. 4, where  $\theta_o = 0$  and  $\theta_r$  is approximately 33 degrees, Equation (1) would be reduced to

20

$$\theta = 1.88\lambda / nL \quad (2)$$

25

Once the minimum angular spacing is determined, the servo blocks may then be recorded, in the conventional manner, known by those skilled in the art. Servo blocks are recorded with a preferred holographic recording

system 30, illustrated in Fig. 10. The system 30 includes a signal producing light source 31, a beam splitter 32 which splits a signal 43 into object beam 44 and reference beam 42, a rotatable reflecting mirror 33 having two (2) degrees of freedom for changing the reference angle  $\theta_r$ , a reflecting mirror 35, an SLM 34 for converting an electrical signal to an optical signal by modulating the object beam 44, reducing lenses 36 and 37, a photorefractive crystal 38 for recording holograms, a detector array 39 and a voice-coil motor (VCM) 41 for rotating reflecting mirror 31 in response to position feedback information detected by array 39. The SLM 34 has an approximately 1.0" x 0.8" viewing area, providing an approximately 640x480 pixel area for modulating the object beam. The detector array 39 may be any known in the art e.g. a charge coupled device (CCD) having an approximately 0.5" x 0.4" viewing area, providing an approximately 1134 x 486 pixel area. The crystal 38 is Fe-LiNbO<sub>3</sub> and disk shaped, approximately 2 mm thick and 70 mm diameter.

In accordance with conventional holographic recording practices, each servo pattern is recorded in the crystal 38 by illuminating a servo pattern bearing object beam 44 with a reference beam 42, at a particular reference angle, to form an interference grating in the crystal 38.

In one preferred embodiment, each servo block is defined by a five spot pattern, shown in Fig. 3 as A, B, C, D, and E. The intensity of each of the five spots and the combination thereof represent angular positions of the reference beam and provide position feedback information. As depicted in the Fig. 3 embodiment, the five spots are located around the outer periphery of the data area, which is further represented in Fig. 3 as a symmetrical four sided area. In this embodiment, the spots are arranged as shown to maximize the distance between the pairs of spots which define each of the five servo blocks, thereby optimizing the amount of retrievable data area.

The servo block of Fig. 3 is shown with the reference beam having one axis of freedom, x-axis, as represented by Ax, Bx, Cx, Dx, and Ex being highlighted. A reference beam indexed in the Y-axis would be represented by Ay, By, Cy, Dy, and Ey being highlighted. Those skilled in the art will understand that other variations of the five patterns may be used, including other arrangements, spot locations, and number of spots.

The servo blocks for one axis of freedom, x-axis, are defined by five patterns, A-B, B-C, C-D, D-E and E-A, as illustrated in Figs. 4a - 4e. Each pattern defines a variation of the five spots. For example, pattern A-B is defined by spots A and B being shaded, pattern B-C defined by spots B and C being shaded, pattern C-D defined by spots C and D being shaded, pattern D-E defined by spots D and E being shaded, and pattern E-A defined by spots E and A being shaded. The shaded spots represent intensified images while the non-shaded spots represent non-intensified images. Each servo block pattern is recorded at 0.50 increments, starting with pattern 1 recorded at -0.750, pattern 2 at -0.250, and so forth. As will be explained herein below, each of the servo blocks shown in Figs. 4a - 4e presents feedback information to enable retrieval of each data page with maximum SNR.

Fig. 6 shows a graphical representation of the sinc functions of the five spots (A,B,C,D,E) of a servo block, as a function of angle of incidence, i.e. reference angle,  $\theta_r$ . Thus, as the reference beam is indexed through a range of angles, the intensity of each of the five spots within each servo block varies, as illustrated in Fig. 9. As illustrated therein, each longitudinal band, B1, B2, etc., corresponds to the intensity of each spot as a function of angle of incidence. In addition, each angle of incidence provides a "snapshot" of the servo block, i.e. the relative intensities of each of the five spots. For example, at the angle of incidence of 0.250, the intensity of spot

C would be strongest, while spots B and D would exhibit lesser intensified images.

Once the servo blocks are recorded in the crystal, like any other metastable holograms recorded in a photorefractive medium, the servo blocks may be erased over time, by subsequent illuminations. To "fix" the servo blocks, so as not to be erasable by subsequent illumination, the crystal 38 is heated in accordance with conventional methods, represented by step 300. Typically, an Fe-LiNbO<sub>3</sub> crystal is heated to approximately 150-200 C, where the ions become mobile, for a period of time depending on the dimensions of the crystal.

The crystal 38 is then cooled by quickly removing it from the heat source and air cooling it back to ambient temperature (as represented by step 400). The cooling rate is typically dependent on the thermal shock tolerance of the crystal. The process of "fixing" metastable holograms is well known to those skilled in the art. However, the inventors of the present invention believe that a holographic recording method combining permanent and metastable holograms within the same recording areas is not known in the art and is one of the distinguishing features of the present invention.

It should be noted that during servo block writing on the media, a detector array will not be useful as an angle feedback mechanism, since the media lacks any reference encoding. Analogous to disk drive servo writing, a high accuracy measurement system may be used to determine the angle  $\theta$ , either by an encoder on the beam steering device or by observing both object and reference beams in some other way.

Those skilled in the art will understand that in addition to servo blocks, image space identifiers may be recorded within each image space to provide additional position feedback information. Each identifier may be unique, enabling each image space to be distinguished from others.

Identifiers may be recorded simultaneously with the servo blocks or data pages using techniques described herein above with respect to the servo blocks. In addition, identifiers may also be fixed using the conventional method, also described herein above.

5       Next, as represented by step 500, data pages are recorded in the same image space of the crystal 38 in the conventional manner, as described above in recording the servo blocks. In the preferred embodiment, each data page is recorded at reference angle increments of  $\theta$ , starting at 0. Accordingly, Fig. 5 presents the amplitude of three recorded data pages, D1, 10 D2, and D3, as a function of the angle of incidence. Examining Figs. 5 and 6, concurrently, shows that servo block spots B and C provide nominal position feedback information for data page D1, servo block spots D and E provide nominal position feedback information for data page D2 and servo block spots A and B provide nominal position feedback information for data 15 page D3. For example, at  $\theta = 0$ , spots B and C are equally intensified at approx. 0.8 of normalized power while spots A and D are equally intensified at approx. 0.1 of normalized power, which is represented by servo pattern B-C of Fig. 4b. The relationship of adjacent servo patterns is best illustrated by Fig. 7, which shows the difference of positioning functions as a function 20 of angle of incidence. Function A-B represents the difference in sinc functions of servo block A and B, function B-C represents the difference of sinc functions of servo block B and C, and so forth.

As illustrated in Figs. 7 and 8, several positioning functions exist at each "data page center", i.e. reference angle at which a data page exhibits its 25 highest intensity. However, the most linear positioning function at each data page center would provide the most reliable position feedback information for that data page. Hence, Fig. 8 represents a linearized positioning function as a function of the angle of incidence,  $\theta$ . Accordingly,

between  $-0.25\theta$  and  $0.25\theta$ , servo patterns 2 and 3 provide feedback information for data page 1, between  $0.75\theta$  and  $1.25\theta$ , servo patterns 4 and 5 provide position feedback for data page 2, and so forth. By utilizing the linearized portions of each positioning function, the present invention enables data pages to be tracked in an accurate manner. Note that in the present embodiment, servo blocks are recorded at  $0.5\theta$  increments, resulting in a range of linearized positioning function of  $0.5\theta$ . Those skilled in the art will realize that servo blocks may be recorded at other increments and still retrieve data pages with maximum SNR. However, with increments less than  $0.5\theta$ , the range of linearized positioning function is reduced (see Fig. 8). In addition, with increments greater than  $0.5\theta$ , the range is increased but may include non-linear portions.

It should also be pointed out that the reference angle  $\theta_r$  has two degrees of freedom i.e.  $\theta_r$  may be indexed in the x direction as well as in the y direction, with each increment in each direction corresponding to a different hologram within the same image space. Therefore, as discussed herein above, servo block patterns corresponding to reference angles indexed in the y direction may be recorded along the vertical edges of the periphery of an image space, illustrated in Fig. 3. Once the minimum angular spacing  $\theta$  is determined, the write process may begin, and the order in which the servo blocks are written is not constrained. The important characteristics are that adjacent servo blocks are exposed at nearly the same efficiency and are accurately spaced apart at  $0.5\theta$  increments.

In one improvement over the system 10 shown in Fig. 1, the present invention incorporates the position feedback information as described above to fine tune the reference angle and maximize SNR of the recorded signal by reducing crosstalk.

In reconstructing a data page, (represented by step 600), a reference beam illuminates the crystal at a specific reference angle. Depending on the reference angle, partial images of the data page and servo patterns may be generated on the detector array 39. For example, propagating a reference beam at the crystal at an angle of incidence of  $0.75\theta$  would reconstruct partial images of data pages recorded at reference angles 0 and  $\theta$  (indicated by Fig. 5) indicating crosstalk, as well as position feedback information in the form of servo patterns 3, 4, and 5, (indicated by Fig. 6). According to Fig. 8, either positioning function 3-4 or 4-5 may be utilized to retrieve data page D1 or D2, respectively. As position feedback information is transmitted to a voice coil motor (VCM) 41, the VCM rotates reflecting mirror 31 to adjust the reference angle. As a result, SNR is maximized and crosstalk is minimized as the reconstructed data page achieves maximum diffraction efficiency and intensity. Alternatively, a reference beam illuminating the crystal at an angle of incidence of  $1.0\theta$  would reconstruct data page D2, with maximum SNR and minimum crosstalk (as indicated by Fig. 5), as well as servo patterns 1, 3, 4, and 5. As illustrated in Fig. 9, servo patterns 1 and 3 would exhibit equal intensity, as would servo patterns 4 and 5.

Those skilled in the art will also understand that other means may be applicable for adjusting the angle of incidence of the reference beam, in response to position feedback information. For example, the crystal may be rotated by a voice coil motor or a stepper motor to adjust the angle of incidence.

In accordance with principles of the present invention, servo blocks may also be applicable to wavelength multiplexing. The application being similar to that described herein above with respect to angular multiplexing. Specifically, once a minimum wavelength spacing is determined servo

blocks may be recorded at  $\omega/2$  intervals while data pages would be recorded at intervals of  $\omega$ . The details of determining the minimum wavelength spacing is well known to those skilled in the art. For example the Hong et al. article entitled "Volume Holographic Memory Systems: Techniques and  
5 Architectures" discloses minimum frequency spacing as

$$[2\pi\Delta v/(c/n)](1+\cos\theta_r)$$

where  $v$ =optical frequency,  $\theta_r$  = reference angle, and  $n$ = refractive index of  
10 the crystal. Additionally, separate servo blocks must be recorded for each type of multiplexing, i.e. angular and wavelength multiplexing. Both angular and wavelength multiplexing techniques may be used separately or in combination.

To those skilled in the art, many changes and modifications will be  
15 readily apparent from consideration of the foregoing description of a preferred embodiment without departure from the spirit of the present invention, the scope thereof being more particularly pointed out by the following claims. The descriptions herein and the disclosures hereof are by way of illustration only and should not be construed as limiting the scope of  
20 the present invention which is more particularly pointed out by the following claims.

What is claimed is:



1. A method of holographic recording in a photorefractive medium comprising the steps of:

recording a plurality of servo blocks within an image space in the medium; and

5 recording a plurality of data pages within the image space in the medium.

2. The method of claim 1 wherein each servo block provides position feedback information and is generated by illuminating the medium  
10 with a servo block reference beam and a servo block object beam to effect the migration of charges in the medium, each servo block reference beam and servo block object beam being incident upon a face of the medium at a servo block reference angle, the servo block reference angle defining the angle between the servo block reference beam and the servo block object  
15 beam.

3. The method of claim 1 wherein each of the data pages is defined by an interference grating generated by illuminating the medium with a data page reference beam and a data page object beam to effect the  
20 migration of charges in the medium, each data page reference beam and data page object beam being incident upon the face of the medium at a data page reference angle, the data page reference beam defining the angle between the data page reference beam and the data page object beam.

25 4. The method of claim 1 further comprising the step of converting the plurality of servo blocks into a plurality of permanent holograms that cannot be erased by subsequent illumination of the medium.

5. The method of claim 4 wherein the step of converting the plurality of servo blocks further comprises the step of heating the medium.

6. The method of claim 1 wherein the servo blocks provide means  
5 for reconstructing one of the data pages with substantially no crosstalk from other data pages.

7. The method of claim 1 wherein each of the servo blocks is  
10 located around the periphery of the image space in the medium.

8. The method of claim 2 wherein the servo block object beam and the servo block reference beam are generated with a coherent monochromatic light source.

9. The method of claim 3 wherein the data page object beam and  
15 the data page reference beam are generated with the coherent monochromatic light source.

10 The method of claim 2 wherein each of the servo block  
20 reference angles is separated by approximately half of a minimum angular spacing of the medium.

11. The method of claim 3 wherein each of the data page reference  
25 angles is separated by the minimum angular spacing of the medium.

12. The method of claim 1 further comprising the step of recording an image space identifier within each of a plurality of image spaces in the

medium, each identifier providing means for distinguishing each of the image spaces.

13. The method of claim 12 further comprising the step of  
5 converting the image space identifiers into permanent holograms that cannot be erased by subsequent illumination of the medium.

14. A method of holographic recording in a photorefractive medium comprising the steps of :

10 recording a first servo block in the medium, the first servo block being defined by a first interference grating, the first grating being generated by illuminating the medium with a first reference beam and a first object beam to effect the migration of charges in the medium, the first servo block reference beam and the first servo block object beam being incident upon a  
15 face of the medium at a first servo block reference angle, the first servo block reference angle defining the angle between the first servo block reference beam and the first servo block object beam;

recording a second servo block in the medium, the second servo block being defined by a second interference grating, the second grating being  
20 generated by illuminating the medium with a second reference beam and a second object beam to effect the migration of charges in the medium, the second servo block reference beam and the second servo block object beam being incident upon the face of the medium at a second servo block reference angle, the second servo block reference angle defining the angle  
25 between the second servo block reference beam and the second servo block object beam;

recording a third servo block in the medium, the third servo block being defined by a third interference grating, the third grating being

generated by illuminating the medium with a third reference beam and a third object beam to effect the migration of charges in the medium, the third servo block reference beam and the third servo block object beam being incident upon the face of the medium at a third servo block reference angle, the third servo block reference angle defining the angle between the third servo block reference beam and the third servo block object beam;

recording a fourth servo block in the medium, the fourth servo block being defined by a fourth interference grating, the fourth grating being generated by illuminating the medium with a fourth reference beam and a fourth object beam to effect the migration of charges in the medium, the fourth servo block reference beam and the fourth servo block object beam being incident upon the face of the medium at a fourth servo block reference angle, the fourth servo block reference angle defining the angle between the fourth servo block reference beam and the fourth servo block object beam;

recording a fifth servo block in the medium, the fifth servo block being defined by the first interference grating, the fifth servo block being generated by illuminating the medium with the fifth reference beam and the fifth object beam to effect the migration of charges in the medium, the fifth servo block reference beam and the fifth servo block object beam being incident upon the face of the medium at a fifth servo block reference angle, the fifth servo block reference angle defining the angle between the fifth servo block reference beam and the fifth servo block object beam;

recording a first data page in the medium, the first data page being defined by a first data page interference grating, the first data page grating being generated by illuminating the medium with a first data page reference beam and a first data page object beam to effect the migration of charges in the medium, the first data page reference beam and the first data page object beam being incident upon the face of the medium at a first data page

reference angle, the first servo block reference angle defining the angle between the first data page reference beam and the first data page object beam;

5 recording a second data page in the medium, the second data page being defined by a second data page interference grating, the second data page grating being generated by illuminating the medium with a second data page reference beam and a second data page object beam to effect the migration of charges in the medium, the second data page reference beam and the second data page object beam being incident upon the face of the  
10 medium at a second data page reference angle, the second data page reference angle defining the angle between the second data page reference beam and the second data page object beam; and

recording a third data page in the medium, the third data page being defined by a third data page interference grating, the third data page grating  
15 being generated by illuminating the medium with a third data page reference beam and a third data page object beam to effect the migration of charges in the medium, the third data page reference beam and the third data page object beam being incident upon the face of the medium at a third data page reference angle, the third data page reference angle defining the angle  
20 between the third data page reference beam and the third data page object beam.

15. The method of claim 14 further comprising the step of  
converting each of the servo blocks into holograms that cannot be erased by  
25 subsequent illumination;.

16. The method of claim 14 wherein the second and third servo blocks provide position feedback information during reconstruction of the first data page.

5        17. The method of claim 14 wherein the fourth and fifth servo blocks provide position feedback information during reconstruction of the second data page.

10       18. The method of claim 14 wherein each of the servo blocks is defined by one of five patterns.

19. The method of claim 18 wherein each of the five patterns is recorded about a periphery of the image space.

15       20. The method of claim 18 wherein each of the five patterns is defined by a five spot arrangement.

20       21. The method of claim 14 wherein the reference beams, object beams, data page reference beams and data page object beams are each propagated with a same wavelength.

22. The method of claim 14 wherein adjacent data pages are recorded at an angular spacing of a minimum angular spacing of the crystal.

25       23. The method of claim 14 wherein adjacent servo blocks are recorded at angular increments of approximately one-half of the minimum angular spacing.

24. A method for retrieving holograms recorded within an image space in a photorefractive medium comprising the steps of:

5 recording a plurality of servo blocks within the image space in the medium, each servo block containing position feedback information and being defined by an interference grating generated by illuminating the medium with a servo block reference beam and a servo block object beam to effect the migration of charges in the medium, each servo block reference beam and servo block object beam being incident upon a face of the medium at a servo block reference angle, the servo block reference angle defining the angle between the servo block reference beam and the servo block object beam;

converting each of the plurality of servo blocks into permanent spatially varying index of refraction patterns in the medium that cannot be erased by subsequent illumination;

15 recording a plurality of data pages within the image space in the medium, each of the data pages being defined by an interference grating generated by illuminating the medium with a data page reference beam and a data page object beam to effect the migration of charges in the medium, each data page reference beam and data page object beam being incident upon the face of the medium at a data page reference angle, the data page reference beam defining the angle between the data page reference beam and the data page object beam;

20 reconstructing one of the data pages and position feedback information on a detector array by propagating the data page reference beam at the face of the medium at a reference angle; and

adjusting the data page reference angle in response to the position feedback information.

25. A method of holographic recording in a photorefractive medium comprising the steps of:

- 5 recording a plurality of servo blocks within an image space in the medium, each servo block providing position feedback information and being defined by an interference grating generated by illuminating the medium with a servo block reference beam and a servo block object beam to effect the migration of charges in the medium, each servo block reference beam and servo block object beam being incident upon a face of the medium and defined by a servo block reference wavelength; and
- 10 recording a plurality of data pages within the image space in the medium, each of the data pages being defined by an interference grating generated by illuminating the medium with a data page reference beam and a data page object beam to effect the migration of charges in the medium, each data page reference beam and data page object beam being incident
- 15 upon the face of the medium and defined by a data page reference wavelength.

26. The method of claim 24 wherein a servo block reference angle defined between each servo block reference beam and each servo block object beam remains fixed.

20

27. The method of claim 24 wherein a data page reference angle defined between each data page reference beam and each data page object beam remains fixed.

25

28. An apparatus for retrieving holograms recorded with position feedback information within an image space in a photorefractive medium comprising:



- means for generating a beam of light;
- means for splitting the beam of light into an object beam and a reference beam;
- a spatial light modulator for modulating the object beam;
- 5      optical means for directing the object beam and reference beam incident upon a face of the medium at a reference angle therein between;
- a detector array for converting the optical signal to an electrical signal; and
- means for receiving the position feedback information and adjusting
- 10    the reference angle in response to the position feedback information.

29. A method for retrieving holograms recorded within a plurality of image spaces in a photorefractive medium comprising the steps of:


- recording a plurality of servo blocks within the image spaces in the
- 15    medium, each servo block containing position feedback information and being defined by an interference grating generated by illuminating the medium with a servo block reference beam and a servo block object beam to effect the migration of charges in the medium, each servo block reference beam and servo block object beam being incident upon a face of the medium
- 20    at a servo block reference angle, the servo block reference angle defining the angle between the servo block reference beam and the servo block object beam;
- converting each of the plurality of servo blocks into permanent spatially varying index of refraction patterns in the medium that cannot be
- 25    erased by subsequent illumination;
- recording an image space identifier within each of the image spaces, each identifier providing means for distinguishing each of the image spaces;

recording a plurality of data pages within the image spaces in the medium, each of the data pages being defined by an interference grating generated by illuminating the medium with a data page reference beam and a data page object beam to effect the migration of charges in the medium,  
5 each data page reference beam and data page object beam being incident upon the face of the medium at a data page reference angle, the data page reference beam defining the angle between the data page reference beam and the data page object beam;

reconstructing one of the data pages and position feedback  
10 information from an image space, on a detector array, by propagating the data page reference beam at the face of the medium at a reference angle; and  
adjusting the data page reference angle in response to the position feedback information.


15

1/8



**FIG. 1**  
PRIOR ART

2/8

**FIG. 2**

3/8




FIG. 3

4/8




FIG. 4c




FIG. 4b




FIG. 4e




FIG. 4a






FIG. 4d

5/8



7/8




FIG. 9



6/8




FIG. 7




FIG. 8




FIG. 10

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/07780

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC(6) : G02B 1/28; G01B 11/00; G11C 13/04; G11B 7/00 US CL : 359/4, 24; 369/103; 365/125; 356/138 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) U.S. : 359/4, 24; 369/103; 365/125; 356/138 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched 359/3, 7, 21, 22, 558; 356/139, 347, 348, 399, 400; 365/124, 125, 216, 234, 235; 369/109 Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) APS diffraction grating, hologram, angle, angular?, align?		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,319,629 A (HENSHAW ET AL) 07 June 1994 (07.06.94), see entire document.	1-29
X	US 3,936,139 A (HUIGNARD ET AL) 03 February 1976 (03.02.76), see entire document.	28
X	US 5,436,867 A (MOK) 25 July 1995 (25.07.95), see entire document.	28
X	US 5,450,218 A (HEANUE ET AL) 12 September 1995 (12.09.95), see entire document.	28
X	US 5,422,873 A (KEWITSCH ET AL) 06 June 1995 (06.06.95), see entire document.	28
X	US 3,847,465 A (MICHIRON ET AL) 12 November 1974 (12.11.74), see entire document.	28
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art *&* document member of the same patent family	
Date of the actual completion of the international search 29 JULY 1997		Date of mailing of the international search report 08 AUG 1997
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer JON W. HENRY Telephone No. (703) 305-6106

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/07780

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,483,365 A (PU ET AL) 09 January 1996 (09.01.96), see entire document.	28
X	US 5,416,616 A (JENKINS ET AL) 16 May 1995 (16.05.95), see entire document.	28
X	US 3,847,465 A (MICHIRON ET AL) 12 November 1974 (12.11.74), see entire document.	28